



FEATURES

- Direct Bury Installation
- Tenon or Side Mount
- 1" PVC Wireway
- Handhole Access for Wiring
- Wireway 90 for Conduit Entry

APPLICATIONS

- Parking Lots
- Roadway
- General Area



Pole Ordering/Specifying Information

PCST		
SERIES	Length ____ Feet	Mounting T 2" Tenon T3 3" Tenon CD Custom Drill

Pole Specifications - Sand Applications

Pole	Overall Height	Mounting Height	Burial Depth	Tip"/Butt"	Weight	EPA 150 MPH	EPA 170 MPH	EPA 180 MPH
PCST-17	17	10	7	4.5/7.25	600	10.8	6.6	5.0
PCST-22	22	15	7	4.5/8.0	900	7.6	4.2	2.9
PCST-28	28	20	8	5.0/9.5	1,530	9.8	5.0	3.2
PCST-34	34	25	9	5.0/10.5	2,130	12.0	6.2	3.8
PCST-40	40	30	10	6.0/12.5	3,560	15.0	7.2	4.4
PCST-45	45	35	10	6.0/13.3	4,180	8.7	1.6	--
PCST-46	46	35	11	6.0/13.5	4,570	18.1	8.9	5.5
PCST-51	51	40	11	6.5/14.8	6,060	12.0	3.0	--
PCST-58	58	45	13	6.5/16.0	7,700	29.8	16.0	10.8
PCST-63	63	50	13	6.5/16.8	9,030	28.2	14.8	9.6

EPAs are Approximate and need to be Confirmed and Certified by a Registered Professional Engineer
 Specifications Subject to Change

Pole Specifications - Rock Applications

Pole	Overall Height	Mounting Height	Burial Depth	Tip"/Butt"	Weight	EPA 150 MPH	EPA 170 MPH	EPA 180 MPH
PCST-15	15	10	5	4.5/7.0	500	11.0	7.0	3.0
PCST-22	22	15	7	4.5/8.1	1,200	26.0	18.0	14.0
PCST-27	27	20	7	5/9.38	1,440	17.0	8.0	4.0
PCST-32	32	25	7	5.0/10.0	1,920	14.0	9.0	5.0
PCST-37	37	30	7	6.0/12.0	3,110	13.0	8.0	5.0
PCST-43	43	35	8	6.0/13.0	4,050	17.7	7.1	4.4
PCST-50	50	40	10	6.5/14.6	5,840	23.8	15.8	11.5
PCST-55	55	45	10	6.5/15.5	6,970	31.0	12.6	8.2
PCST-60	60	50	10	6.5/16.2	8,220	27.0	9.9	5.2

EPAs are Approximate and need to be Confirmed and Certified by a Registered Professional Engineer
 Specifications Subject to Change



PROJECT		SOUTHEAST POLES		
TYPE	QTY			
NOTES		TITLE Square Tapered Concrete Pole		
APPROVAL		DRAWING/FILE SE Pole and Bracket Catalog.xlsx		
		DATE 4/26/2018	SCALE N.T.S.	SHEET 2 OF 2