


**FEATURES**

- Extruded Aluminum Tube
- Solid Aluminum Base Plate
- Solid Aluminum Gussets
- All Parts Circumferentially Welded
- Bronze Finish with Optional Colors
- Side or Tenon Mount
- Mounting Heights up to 30 Feet
- Normal Duty .125 Wall
- Medium Duty .188 Wall
- Heavy Duty .250 Wall
- S Strengthening Process Option
- Handhole Access for Wiring
- Pole Base Cover Included
- Optional Bolts
- Foundation Sold Separately
- Use CBR-24 or Field Cast

**APPLICATIONS**

- Parking Areas
- Roadway
- General Area



# PAR Series

# Round Aluminum Pole - Anchor Base

## Pole Ordering/Specifying Information

<b>PAR</b>						
<b>SERIES</b>	<b>Size</b> 4 4" 5 5" 6 6"	<b>Length</b> ___ Feet	<b>Color</b> BZ Bronze CC Custom Color	<b>Duty</b> ND Normal MD Medium HD Heavy S Strength Process	<b>Mount</b> _ Drill/Cap T 2.38" Tenon	<b>Options</b> AB Bolts

## Pole Specification Table

Pole	Length	Size	Wall Thickness	Bolt Circle	Base Plate Sq/Thick	Bolts		
PAR-4-10-ND	10	4"	0.125	8.5"-11"	10.65"/.75"	5/8" X 18"	-	-
PAR-4-12-ND	12	4"	0.125	8.5"-11"	10.65"/.75"	5/8" X 18"	-	-
PAR-4-14-ND-S	14	4"	.125-S	8.5"-11"	10.65"/.75"	5/8" X 18"	-	-
PAR-4-15-ND-S	15	4"	.125-S	8.5"-11"	10.65"/.75"	5/8" X 18"	-	-
PAR-5-15-MD	15	5"	0.188	8.5"-11"	10.65"/.75"	3/4" x 24"	-	-
PAR-5-16-MD	16	5"	0.188	8.5"-11"	10.65"/.75"	3/4" x 24"	-	-
PAR-5-18-MD	18	5"	0.188	8.5"-11"	10.65"/.75"	3/4" x 24"	-	-
PAR-5-20-MD	20	5"	0.188	8.5"-11"	10.65"/1"	3/4" x 30"	-	-
PAR-5-20-MD-S	20	5"	.188-S	8.5"-11"	10.65"/1"	3/4" x 30"	-	-
PAR-5-25-MD-S	25	5"	.188-S	8.5"-11"	10.65"/1"	1" x 36"	-	-
PAR-6-25-MD-S	25	6"	.25-S	11"-13"	12"/1.5"	1" x 36"	-	-
PAR-6-30-MD-S	30	6"	.25-S	11"-13"	12"/1.5"	1" x 36"	-	-

## EPA

Pole	120 MPH	140 MPH	150 MPH	160 MPH	170 MPH	180 MPH		
PAR-4-10-ND	4.1	2.8	2.3	1.9	1.7	1.5	-	-
PAR-4-12-ND	2.9	1.9	1.4	1.2	1.0	0.8	-	-
PAR-4-14-ND-S	5.1	3.3	2.5	2.1	1.8	1.5	-	-
PAR-4-15-ND-S	4.4	2.8	2.2	1.8	1.5	1.3	-	-
PAR-5-15-MD	5.8	4.1	3.5	2.9	2.5	2.2	-	-
PAR-5-16-MD	4.8	3.4	2.9	2.5	2.1	1.9	-	-
PAR-5-18-MD	3.7	2.6	2.2	1.8	1.6	1.4	-	-
PAR-5-20-MD	2.8	1.9	1.6	1.3	1.1	0.9	-	-
PAR-5-20-MD-S	9.6	6.8	5.8	4.9	4.2	3.7	-	-
PAR-5-25-MD-S	5.6	3.8	3.1	2.6	2.1	1.8	-	-
PAR-6-25-MD-S	13.1	9.4	8.0	6.8	5.9	5.2	-	-
PAR-6-30-MD-S	11.8	8.5	7.2	6.1	5.3	4.7	-	-

EPA's are Approximate and need to be Confirmed and Certified by a Registered Professional Engineer  
 Strengthening Process can be Modified to Produce Higher EPA's  
 Consult Factory  
*Specifications Subject to Change*



<b>PROJECT</b>		<b>SOUTHEAST POLES</b>		
<b>TYPE</b>	<b>QTY</b>			
<b>NOTES</b>		<b>TITLE</b> Round Aluminum Pole - Anchor Base		
<b>APPROVAL</b>		<b>DRAWING/FILE</b> SE Pole and Bracket Catalog.xlsx		
		<b>DATE</b> 4/26/2018	<b>SCALE</b> N.T.S.	<b>SHEET</b> 2 OF 2