



FLM LED Series

SPECIFICATIONS

- Die Cast Aluminum Housing
- Tempered Clear Flat Glass Lens
- Bronze Powder Coat Finish, Optional Custom Color
- CRI LED Aluminum Substrate Board
- Universal Volt LED Driver 120-277V, Optional 480V
- 3K, 4K or 5K LED Color Options
- Optional Surge Protection
- Optional Dimming
- Optional Wire Guard, Glare Shield or Vandal Guard

APPLICATIONS

- General Area/Flood Lighting
- Walkways, Parking, Roadway, Area
- Schools, Commercial Buildings, Communities
- Street Lighting, Car Lots, Campuses

ELECTRICAL

- 120-277V; 50/60Hz
- Optional 480V; 50/60Hz
- 37 Watts; 4,066 Lumens

INSTALLATION

- Mounts with 1/2" Threaded Knuckle or Optional Adjustable Slip Fitter

CERTIFICATIONS/LISTINGS

- CSA Listed
- IP65
- Listed for Wet Locations



PROJECT _____ TYPE _____

QTY _____ NOTES _____ APPROVAL _____

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: FLM L 37 40K UNV



Series

Light Source

L Light Emitting Diodes

Nominal Watts

37 37 Watts

LED Color

- 30K 3000K LED
- 40K 4000K LED
- 50K 5000K LED


Volts

UNV 120-277V
480 480V


Options

- ASF Adjustable Slip Fitter
- SP Surge Protection
- D10 0-10V Dimming
- WG Wire Guard
- GS Glare Shield
- VG Vandal Guard
- CC Custom Color


SPECIFICATIONS



OPTIONS/ACCESSORIES




ASF Adjustable Slip Fitter




WG Wire Guard



GS Glare Shield



VG Vandal Guard



Specifications Subject to Change

