

WPSG Series

Small Glass Wall Pack



WPSG Series

SPECIFICATIONS

- Die Cast Aluminum Housing
- Borosilicate Molded Glass Lens
- Bronze Powder Coat Finish, Optional Custom Color
- Internal Aluminum Reflector (Non LED)
- HID Porcelain Medium Base 4KV Socket (Non LED)
- Stainless Steel Hardware
- Multiple Light Source Options
- 3K, 4K or 5K LED Color Options
- Universal Volt LED Driver with Optional Dimming
- Optional Photocell
- Optional Surge Protection
- Optional Wire Guard, Glare Shield and Full Cut Off

APPLICATIONS

- General Area, Facade Lighting, Entry Lighting
- Platforms, Walkways, Parking, Tunnels
- Schools and Universities
- Commercial, Warehouse, Industrial Facilities

ELECTRICAL

- 120-277V: LED 23W
- 120V: HPS 35W, 50W, 70W, 100W & 150W
- Quad Volt: HPS 50W, 70W & 100W, MH 50W, 70W, & 100W

INSTALLATION

- Mounts Over Recessed Box or with Surface Conduit

CERTIFICATIONS/LISTINGS

- CSA Listed
- Listed for Wet Locations

ALL-SITE LIGHTING

PROJECT _____ TYPE _____


QTY _____ NOTES _____ APPROVAL _____

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: WPSG M 100 Q L

WPSG					
Series					Options
	Light Source		LED Color		
	M Metal Halide H High Pressure Sodium L Light Emitting Diodes		___ Non LED 30K 3000K LED 40K 4000K LED 50K 5000K LED		L Lamped PC Photocell D10 0-10V Dimming (LED) SP Surge Protection FC Full Cut Off GS Glare Shield WG Wire Guard CC Custom Color
		Watts		Volts	
		MH HPS LED		120 120V	
		50 35 23		UNV 120-277V	
		70 50		Q 120/208/240/277V	
		100 70			
		100			
		150			


SPECIFICATIONS




OPTIONS/ACCESSORIES



FC Full Cut Off



GS Glare Shield



WG Wire Guard

Specifications Subject to Change

AMERICA LIGHT

America Light, Inc 1489 W 13th St Riviera Beach FL 33404 Phone 561.296.0364 Sales@AmericaLight.com