

# WSM Series

# Medium Semi-Cut Off Wall Pack



WSM Series

### SPECIFICATIONS

- Die Cast Aluminum Housing
- Tempered Clear Flat Glass Lens
- Bronze Powder Coat Finish, Optional Custom Color
- Internal Aluminum Reflector (Non-LED)
- Semi-Cut Off Front Frame
- HID Porcelain Medium Base 4KV Socket or CF Plug-In Type, GX24Q (Non LED)
- Stainless Steel Hardware
- Multiple Light Source Options
- 3K, 4K or 5K LED Color Options
- Universal Volt LED Driver with Optional Dimming
- Optional Emergency Battery (CF/LED)
- Optional Photocell
- Optional Surge Protection
- Optional Wire Guard

### APPLICATIONS

- General Area, Facade Lighting, Entry Lighting
- Platforms, Walkways, Parking, Tunnels
- Schools and Commercial Buildings
- Commercial, Warehouse, Industrial Facilities

### ELECTRICAL

- 120-277V: LED 37W & CF 26W, 32W, 42W, 52W, 64W & 84W
- 120V: HPS 35W, 50W, 70W, 100W, & 150W
- Quad Volt: HPS & MH 50W, 70W, 100W & 150W

### INSTALLATION

- Mounts Over Recessed Box or with Surface Conduit

### CERTIFICATIONS/LISTINGS

- CSA Listed
- Listed for Wet Locations



PROJECT \_\_\_\_\_ TYPE \_\_\_\_\_


QTY \_\_\_\_\_ NOTES \_\_\_\_\_ APPROVAL \_\_\_\_\_

### ORDERING/SPECIFYING INFORMATION:

EXAMPLE: WSM M 100 Q L

WSM					
Series					Options
	Light Source			LED Color	
	M Metal Halide			___ Non LED	L Lamped
	H High Pressure Sodium			30K 3000K LED	PC Photocell
	F Compact Fluorescent			40K 4000K LED	EM 90 Min Battery (CF/LED)
	L Light Emitting Diodes			50K 5000K LED	D10 0-10V Dimming (LED)
					SP Surge Protection
					WG Wire Guard
					CC Custom Color
		Watts		Volts	
		MH HPS CF 2CF LED		120 120V	
		50 35 26 52 37		UNV 120-277V	
		70 50 32 64		Q 120/208/240/277V	
		100 70 42 84			
		150 100			
		150			

### SPECIFICATIONS



### OPTIONS/ACCESSORIES



WG Wire Guard



Specifications Subject to Change

