

Photocontrol - Button Thermal Photocontrol, 120 V Item K4021C



PRODUCT DESCRIPTION

These photocontrols install within lighting fixtures, post lamps, or in-wall boxes to provide dusk-to-dawn ON/OFF control of outdoor lighting.

FEATURES

- ► Mechanical bimetal switch with Cadmium Sulfide photocell
- ► Compact size fits into standard outlet box, post lamp, wall pack and other lighting fixtures
- ► Delay feature prevents unwanted OFF switching
- ▶ 3/8"-18 NPSM, 3/4" long stem with locking nut and washer gasket

APPLICATIONS

- ► Parking Lot Lighting
- ► Landscape Lighting
- Exterior Lighting
- ► Pedestrian Pathway Lighting
- ► Street Lighting

TECHNICAL DATA

General	
Model Number	K4021C
Description	Button Thermal Photocontrol, 120 V
UPC Code	078275002005
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty	2-Year limited
Usage Environments	Outdoor
Photocontrol Type	Thermal
Expected Lifetime (Years)	5
Expected Lifetime (Operations)	3650
Application Compatibilities	HID; Fluorescent; Incandescent
Photocontrol Style	Button
Photocontrol Sensor Location	Front

Control Specifications	
Sensor Time Delay	30 sec to 90 sec
Photocell Type	Cadmium Sulfide
Photo Control Switch Type	Mechanical Bimetal
Fail Mode	ON
Activation On	1 to 5 fc
Activation Off	3 to 15 fc

Dimensions	
Product Height (in)	1 13/16
Product Height (mm)	46
Product Width (in)	15/16
Wire Lead Length (in)	9

Other Certifications and Compatibilities

California Proposition 65



Wire Size Max #18 AWG

Gray
Polycarbonate
8.3 A, 1000 VA
15 A, 1800 W
Wire leads
120 VAC, 50/60 Hz
0.25
4.88
-40°C70°C
UL
cCSAus

CA Title 20 DEHP



ACCESSORIES



6LV1352 Light Shield Accessory for EK4036S, EK4436SM, K4000 Wall Plate Kit for EK4036S, K4000 Series Button Series Button Photocontrols



K43-WP-KIT Photocontrols



LGLBL Lens Sticker Accessory for EK4000 & K4000 Series Photocontrols