

# ALL Series

# Area Light



ALL Series

### SPECIFICATIONS

- Die Cast Aluminum Housing
- Tempered Clear Flat Glass Lens
- Aluminum Reflector
- Uniformed Poured Silicone Gasket
- Bronze Powder Coat Finish, Optional Custom Color
- HID Porcelain Mogul Base 5KV Socket
- Standard Distribution Type IV
- Stainless Steel Hardware
- Multiple Light Source Options
- Optional Surge Protection
- Optional Wire Guard or Glare Shield

### APPLICATIONS

- General Area/Pathway Lighting
- Walkways, Parking, Roadway, Area
- Schools, Commercial Buildings, Communities
- Street Lighting, Car Lots, Campuses

### ELECTRICAL

- Quad Volt: HPS 150W, 250W & 400W, MH 100W 150W & PMH 250W, 320W & 400W
- 480V: HPS 150W, 250W & 400W, MH 100W & 150W, PMH 250W, 320W & 400W

### INSTALLATION

- Mounts with 6" Mounting Arm (Round or Square) for Direct Pole Mount or to Slip Fitter or Mounts with Adjustable Slip Fitter, U-Bracket or Large Yoke

### CERTIFICATIONS/LISTINGS

- CSA Listed
- Listed for Wet Locations

# ALL-SITE LIGHTING

PROJECT \_\_\_\_\_ TYPE \_\_\_\_\_


QTY \_\_\_\_\_ NOTES \_\_\_\_\_ APPROVAL \_\_\_\_\_

### ORDERING/SPECIFYING INFORMATION:


EXAMPLE: ALL P 250 Q L

ALL				
Series	Light Source	Volts	Options	
H High Pressure Sodium	M Metal Halide	Q 120/208/240/277V	L Lamped	
P Pulse Start Metal Halide		480 480V	A6 A6" Arm	
			A6R A6"R Arm	
			ASF Adjustable Slip Fitter	
			UB U-Bracket	
			LY Large Yoke	
			SP Surge Protection	
			WG Wire Guard	
			GS Glare Shield	
			CC Custom Color	

### SPECIFICATIONS



### OPTIONS/ACCESSORIES




A6 (R) 6" Arm




ASF Adjustable Slip Fitter




UB U-Bracket



LY Large Yoke



WG Wire Guard



GS Glare Shield

Specifications Subject to Change

