



TLW LED Series

SPECIFICATIONS

- Die Cast Aluminum Housing
- White Powder Coat Reflector
- Tempered Clear Glass Lens
- Bronze Powder Coat Finish, Optional Custom Color
- CRI LED COB
- Universal Volt LED Driver 120-277V
- 41K or TFL Amber LED Color Options
- Stainless Steel Hardware
- Optional Surge Protection
- Optional Dimming

APPLICATIONS

- General Area Lighting
- Building Facade Lighting
- Schools, Commercial Buildings, Universities

ELECTRICAL

- 120-277V; 50/60Hz
- 60 Watt COB; 6,508 Lumens
- 80 Watt COB; 8,212 Lumens

INSTALLATION

- Mounts Over Recessed Box or Surface Conduit

CERTIFICATIONS/LISTINGS

- CSA Listed
- Dark Sky Compliant
- IP66
- Listed for Wet Locations



PROJECT \_\_\_\_\_ TYPE \_\_\_\_\_

QTY \_\_\_\_\_ NOTES \_\_\_\_\_ APPROVAL \_\_\_\_\_

ORDERING/SPECIFYING INFORMATION:

EXAMPLE: TLW L 60 40K UNV



Series

Light Source  
L Light Emitting Diodes

LED Color  
41K 4100K LED  
TFL Turtle LED




Options  
SP Surge Protection  
D10 0-10V Dimming  
CC Custom Color

Nominal Watts  
60 60 Watts  
80 80 Watts

Volts  
UNV 120-277V

SPECIFICATIONS



OPTIONS/ACCESSORIES

Specifications Subject to Change

